



## THERMAL CEILING INSULATION

GreenStuf® Thermal Ceiling Insulation is a 100% polyester thermal insulation manufactured to order and pre-cut to nominated width for walls, roof-ceilings, floor and mid-floor applications.

### APPLICATIONS

GreenStuf Thermal Ceiling Insulation is designed for the thermal (and acoustic) insulation of buildings in accordance with New Zealand Building Code (NZBC) H1 Energy Efficiency, and G6 Acoustic Design requirements.

GreenStuf Thermal Ceiling Insulation can be used as a roof blanket, in ceilings, under floors, internal and external walls and in mid-floor cavities. To ensure Building Code compliance, architects and building designers are advised to consult an engineer or the relevant NZ standards before specifying thermal and acoustic insulation products. For information and assistance please contact your GreenStuf account manager.

### TECHNICAL

**Durability:** GreenStuf has a 50 Year Durability Warranty.

**Hazardous Building Materials:** GreenStuf is non-hazardous.



**Declare.**



**NZBC Compliance:** When installed in accordance with the manufacturer's instructions, GreenStuf insulation will satisfy the 50 year durability clause NZBC B2.3.1 (a). GreenStuf meets the relevant clauses of NZBC E3 Internal Moisture, F2 Hazardous Building Materials, and will contribute to meeting H1 Energy Efficiency.

| R-Value                              | Thickness | Width        | Form | Nominal GSM | Nominal Density (kg/m <sup>3</sup> ) | Thermal Conductivity (W/mK) |
|--------------------------------------|-----------|--------------|------|-------------|--------------------------------------|-----------------------------|
| R2.9 Thermal Ceiling Insulation Slab | 115mm     | 870mm        | Slab | 2650        | 23.0                                 | 0.040                       |
| R3.4 Thermal Ceiling Insulation Roll | 140mm     | 580 - 870 mm | Roll | 2550        | 18.2                                 | 0.041                       |
| R3.6 Thermal Ceiling Insulation Pads | 140mm     | 360 - 560 mm | Pads | 3100        | 22.1                                 | 0.038                       |
| R3.6 Thermal Ceiling Insulation Roll | 210mm     | 580 - 870 mm | Roll | 2050        | 9.8                                  | 0.057                       |
| R4.1 Thermal Ceiling Insulation Roll | 210mm     | 870mm        | Roll | 2750        | 13.1                                 | 0.048                       |

**Fire Regulations:** GreenStuf insulation may not be suitable for all applications, as stipulated in the NZBC. Please consult a fire engineer when specifying GreenStuf insulation or contact your GreenStuf account manager for further information.

**Moisture:** GreenStuf is not affected by moisture. Exposure to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption by weight of less than 0.03%.

**Acoustic Performance:** GreenStuf insulation will assist sound reduction by reducing the resonating noise inside the construction cavity. Actual performance will vary with different construction systems. For acoustic design assistance please contact your GreenStuf account manager.

**VOC Emission Safe:**

VOC concentration: 0.01 mg/m<sup>3</sup> (7 days).

GECA/GreenGuard Limit: 0.25 mg/m<sup>3</sup> (7 days).

Cetec Pty Ltd (Report: RCV080408)

**Fire ratings:**ISO 9705: 1993

Classification: Group 1-S

Smoke Production Rate: <5.0m<sup>2</sup>/s

As required by NZBC C/VM2

FAR 4045-2 issued 8<sup>th</sup> October, 2013AS1530.3

Ignitability Index (0-20) 0

Heat Evolved Index (0-10) 0

Spread of Flame Index (0-10) 0

Smoke Developed Index (0-10) 3

APL Report 98055 (Test conducted on GreenStuf Thermal Insulation)

IEC 60695-11-5 (Downlight Fire Test Standard)

GreenStuf has been tested and assessed as complying with IEC 60695-11-5 Needle-flame Test.

Certificates available on request

**Non-Corrosive:** GreenStuf polyester is considered non-corrosive based on AS/NZS 4859.1 Standard for insulation.**Non-Toxic, Non-Allergenic, Non-Irritant:** There are no known hazards with the use or handling of GreenStuf polyester.**Vermin:** GreenStuf is naturally resistant to insect and vermin attack.**Installation:** GreenStuf recommends that all thermal and acoustic insulation be installed in accordance with the manufacturer's instructions (included in each GreenStuf pack) and NZS 4246 Energy Efficiency - Installing Insulation in Residential Buildings.

With a drained cavity wall construction and stud spacings greater than 450mm, NZBC E2/AS1, 9.1.8.5 Wall Framing behind Cavities, requires stud straps to prevent insulation bulging into the cavity. Straps must be run at 300mm centres over the wall underlay.

**Double Layer:** For higher R-value installations we recommend a 'double-layer' installation to reduce thermal bridging and heat-loss through the timber construction. Lay the first layer between the ceiling joists and over the ceiling battens, and the second layer at right angles to, and over the top leaving no gaps except

around heating flues, chimneys, non-CA/IC rated recessed light fittings and non-ducted extractor fans as detailed in our installation instructions.

**MSDS:** Material Safety Data Sheets (MSDS) are available on request from your GreenStuf account manager or by visiting our website [www.greenstuf.co.nz](http://www.greenstuf.co.nz)**Specification & Substitution:** GreenStuf specification documents are available through Masterspec or can be downloaded from our website ([www.greenstuf.co.nz](http://www.greenstuf.co.nz)). Substitution of any products in NZBC compliant systems should not be accepted and we recommend this be made clear in all specification and tender documents.**ISO Standards:** GreenStuf is committed to Quality and Environmental best practice through our ISO 9001 & ISO 14001 certified Quality and Environmental Management Systems.**Take Back Programme:** GreenStuf is recyclable. GreenStuf will gladly recycle used, uncontaminated GreenStuf insulation to help keep it out of landfills. For more information on recycling GreenStuf contact us 0800 428 839.**Packaging Recycling:** GreenStuf packaging is recyclable LDPE 4. Please refer to your local recycling centres for drop off and collection services.**Environmental:** All GreenStuf products are manufactured using 100% polyester fibre and contain a minimum of 50% previously recycled fibre (from PET plastic). GreenStuf products are manufactured under GreenStuf's Zero Waste Programme where all manufacturing waste is recycled back into the production process.

GreenStuf products are Global GreenTag GreenRate Level A certified and can be used to contribute to Green Star and Homestar accreditation.

GreenStuf is also Declare certified to be Red List chemical free and can be used in Living Building Challenge projects. For more information, please contact your GreenStuf account manager, or visit our website [www.greenstuf.co.nz](http://www.greenstuf.co.nz)

AN ISO 9001 AND ISO 14001 CERTIFIED COMPANY

**GreenStuf® Factory and Collections**

40 Westpoint Drive,  
 Hobsonville, Auckland 0618,  
 New Zealand  
 Freephone 0800 428 839  
 Phone +64 9 828 9179  
 Fax +64 9 828 5810  
[www.greenstuf.co.nz](http://www.greenstuf.co.nz)

The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2020 Autex Industries Ltd. All Rights Reserved.

It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your GreenStuf® account manager.