



Acoustic Timber™ Panel

Technical Product Overview

Acoustic Timber™ Panel is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Specification	Product name	Acoustic Timber™ Panel									
	Description	100% polyester lightweight semi-rigid panel									
		Imperial									
	Panel Dimensions	4' x 8'									
		4' x 8' 10"									
	Tolerance	(+0.2") x (+0.4")									
	Thickness	3/8"									
	Tolerance	(+/- 6%)									
		1"									
Physical Description/ Properties	Boiling Point:	N/A									
	Melting Point:	482°F									
	Vapor Pressure:	N/A									
	Specific Gravity:	Polyester 1.38									
	Flash Point:	N/A									
	Explosive Limits:	N/A									
	Solubility in Water:	Not soluble									
	Alkalinity:	pH 7.8									
	Relative Vapour Density:	N/A									
Acoustic Performance	Acoustic Timber Panel is made using Cube™. The effect of the printed surface has been tested and found to have no impact on the acoustic performance of Cube.		Frequency (Hz) 125 250 500 1000 2000 4000 NRC								
	Minimum Noise Reduction Coefficient 0.45		●	3/8" Cube	0.00	0.05	0.15	0.40	0.70	0.85	0.30
			●	1" Cube	0.05	0.20	0.60	0.90	1.00	1.00	0.70
			●	1" Cube (with 1" air gap)	0.15	0.40	0.85	0.95	0.95	0.95	0.80



Product Specifications

Fire Ratings

Acoustic Timber is made from Cube™ which has been tested and evaluated using the following test methods:

ASTM E-84-15a

Class A, FS:24 - SD:250
(Cube™ 3/8")
RJ9445F-1a

Class A, FS:0 - SD:65
(Cube™ 1")
RJ4479-1

CAN/ULC-S102

Class A, FS:0 - SD:10
FS:15 - SD:65
(Cube 3/8")
QA-2243F-3

Suitable Applications

Suitable for use as acoustic and decorative treatments in non-contact areas. For applications where contact is likely to occur, Autex Acoustics recommends our standard Cube™ Panel range.

Acoustic Performance

The ink used to print this surface finish has been tested and found to have no impact on the acoustic performance of Autex Acoustics' products. Please contact your Momentum account manager for further information if required.

Impact Resistance

Acoustic Timber may show surface damage when subjected to impacts. We would advise against using Acoustic Timber in areas where there is likely to be contact with the product.

VOC Emissions

Acoustic Timber has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC and low formaldehyde emissions product. VOC emissions: 0.019 mg/m³ Formaldehyde emissions: <0.005 mg/m³

Color Fastness to Light

Acoustic Timber is suitable for indoor use only. Light fastness is dependent on use and exposure. Acoustic Timber has been evaluated to the following standard:
ISO 105-B02:2014
Rating: 6 (Highest = 7)

Light Reflectance Value (LRV)

Solid Colors

When selecting Acoustic Timber, a sample can be provided and tested for LRV.

Please contact your account manager at the start of your project to arrange a test.

Fabric Care

Avoid contact with the Acoustic Timber surface. Where liquids and other contaminants come in contact with the panels, these should be gently removed immediately and not allowed to soak-in, dry, or set. Refer to the product Care and Maintenance Guide for cleaning guidance. Consult a specialist cleaning company for cleaning if required.

Finish

The acoustic product color may vary from samples and between each product batch. This is due to the inherent nature of the textile. This will not affect the color of the Acoustic Timber.

It is not recommended to pin Acoustic Timber as the printed surface finish is not self-healing, the backing panel color may be visible if pinned.

Blemishes

Due to the nature of the raw material and the manufacturing process, flecks and other small surface blemishes may be visible on the surface of Autex Acoustics panels from time to time. This is an inherent characteristic of the textile products and is unavoidable.

Service

For further information about Acoustic Timber or any other Autex Acoustics product, please contact your Momentum account manager or visit momentumco.com. The information contained in this document is correct to the best of our knowledge at the date of its publication. It is the user's responsibility to determine if this information is suitable for their intended application and to make sure that this document is the most current publication. You can do this by checking our website or contacting your Momentum account manager.

Care and Maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

Autex Acoustics®

M O M E N T U M

momentumco.com

Instagram LinkedIn Pinterest