



**Autex
Acoustics®**

Material Safety Data Sheet

Product Overview

All Autex Acoustics® products are made from 100% polyester fibers with no chemical binders. Available in a range of wall coverings, panels, and ceiling systems. Products are lightweight, easy to install, and are suitable for new buildings and retrofits.

Product Names

3D Ceiling Tiles	Groove™ Panels
3D Tiles	Horizon™
Accent Ceiling Tiles	Lanes™
Acoustic Timber™	Lattice
Cascade™	Mirage™ Textured Panels
Composition®	Quietspace® Panel
Composition® Peel 'n' Stick Tiles	ReForm™
Cove™ / Loch™	Surface Finishes
Cube™	Vertiface®
Frontier™	Verve™ Contoured Panels
Grid Ceiling Tiles	Vicinity™ Workstation Screens
Groove Duet®	

Manufacturer

Autex Industries Ltd 702-718 Rosebank Rd, Private Bag 19988, Avondale 1746, Auckland, New Zealand Freephone 0800 428 839 Phone +64 9 828 9179	Autex Australia Pty Ltd 121-131 Global Avenue, Essendon Fields, VIC 3041, Australia Freephone 1800 678 160 Phone +61 3 9457 6700
--	--

Physical and Chemical Properties

Appearance: Non-woven polyethylene terephthalate (PET) panel	Specific Gravity: Polyester 1.38
Odour: No odor	Flash Point: N/A
pH: 7.8 (pH7 being neutral)	Explosive Limits: N/A
Boiling Point: N/A	Solubility in Water: Not soluble
Melting Point: 482°F (250°C)	Moisture Absorption: Less than 0.4% by weight
Max. Recommended	Relative Vapor
Service Temp: 176°F (80°C)	Density: N/A
Vapor Pressure: N/A	Percent Volatiles: Nil
	Corrosiveness: Non-corrosive

Chemical Stability and Reactivity

Autex Acoustics products are chemically stable. Hazardous reactions will not occur under normal conditions of use and storage. Avoid contact with strong acids, strong bases, or oxidising agents.



Storage and Transport

Packaging as recommended by the manufacturer. Top stow and keep clean and dry. Do not squash or bend product or packaging. Autex Acoustics products are not classified as dangerous goods.

UN Number: Not Allocated
Class: Not Allocated
Hazchem Code: Not Allocated
DOT(US): Not Regulated
IATA: Not Regulated
IMDG: Not Regulated

Moisture Absorption

The structural integrity of Autex Acoustics products will not be affected by moisture. Exposure of Autex Acoustics products to an atmosphere of 120°F at 95% relative humidity for four days showed moisture absorption by weight of less than 0.4%.

Hazards Identification

Autex Acoustics products are considered as non-hazardous and non-dangerous goods.

Fire Hazards

Material will recede away from flame and may drip. Combustion products include carbon oxides (CO, CO₂) and hydrocarbons. Fire fighters and others exposed to combustion products are advised to wear respiratory protective equipment. Extinguishing media: water spray or fog, foam, dry chemical, carbon dioxide. Autex Acoustics products have been tested and assessed for their reaction-to-fire properties. For a copy of the fire certificate or test report for a specific Autex Acoustics product, please contact your Autex Acoustics account manager.

Health Effects/ Personal Protection

There are no known health hazards relating to the use or handling of Autex Acoustics products. No protective clothing is required when handling or installing Autex Acoustics products. Any free fibers which may be present are not of respirable size.

Caution should be taken when cutting Autex Acoustics products. Use of personal protective equipment such as cut resistant gloves and safety glasses is advised. Follow Autex's respective Product Install Instructions, as well as site and individual safe working practices and requirements.

No first aid measures are expected under normal conditions of use, handling, and installation of Autex Acoustics products. If exposed to fumes from combustion of products, move to fresh air and seek medical attention if symptoms persist. If a substantial portion of the product is accidentally ingested, do not induce vomiting and immediately seek medical attention.

Total Volatile Organic Compounds (TVOC) Emissions

Autex Acoustics products are considered as low-emitting products. Autex Acoustics polyester has been tested for TVOC and formaldehyde emissions according to CDPH Standard Method v1.2-2017, with the following results:

After 14 days, office room scenario

TVOC emissions = 0.066 mg/m³

Formaldehyde emissions < 0.004 mg/m³

The measured TVOC and formaldehyde emissions meet the threshold limits set under applicable green building standards and regulations.



Environmental
Information

Autex Acoustics products are manufactured using 100% polyester fiber and contain recycled content (i.e. PET plastic bottles).

Autex Acoustics products are Global GreenTag Green Rate Level A certified.

Autex Acoustics products are verified by Declare to be Red-List Free and can be used in Living Building Challenge projects.

Our commitment to environmental responsibility is demonstrated by our ISO 14001 certified Environmental Management System. For more information, please contact your Autex Acoustics account manager or visit our website.

Disposal
Considerations

Autex Acoustics products with multiple components can be easily disassembled. Untamminated individual components can be reused.

Waste Autex Acoustics products are not hazardous. Dispose in accordance with prevailing laws and regulations, preferably to a recognized collector or contractor.

Zero ODS

Autex Acoustics products manufactured from 100% polyester fiber contain no Ozone Depleting Substances (ODS) listed under the Montreal Protocol.

This MSDS was correct at the time it was prepared (see below for the date). As part of its ISO 9001 certified Quality Management System, Autex Acoustics updates MSDS's when its ongoing review process indicates a need for a change to be made. You should make sure that the MSDS you are reading and relying on is current. You can do this by contacting your Autex Acoustics account manager or by visiting our website.

● **New Zealand**
702-718 Rosebank Road,
Private Bag 19988,
Avondale 1746, Auckland
T 0800 428 839
T +64 9 828 9179
autexacoustics.co.nz

● **Australia**
121-131 Global Avenue,
Essendon Fields,
VIC 3041
T 1800 678 160
T +61 3 9450 6700
autexacoustics.com.au

● **United Kingdom**
Unit J4, Lowfields Way,
Lowfields Business Park,
Elland, West Yorkshire,
HX5 9DA
T +44 0 142 241 8899
autexacoustics.co.uk

● **United States**
742 S Hill Street,
Suite 501, Los Angeles,
CA 90014
T +1 424 203 1813
autexacoustics.com

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), and Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited or other members of the Autex Group. © Copyright 2025 Autex Industries Ltd. All rights reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex Acoustics' account manager.