



Technical Product Overview

3D Ceiling Tiles

3D Ceiling Tiles are manufactured by Autex Industries Ltd under an ISO 9001 and ISO 14001 certified Quality Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a manufacturer's guarantee for a period of no less than 20 years to meet all of the performance properties stated in this guarantee. This guarantee excludes damage caused by daily wear and tear, contamination (including moisture, dust, or stains), fading or discoloration from sunlight exposure, and any issues resulting from incorrect installation or improper maintenance.

Specification

Product Name	3D Ceiling Tiles
Description	100% polyester thermally molded, needle punched tile
	Imperial
Tile Dimensions	23.75" x 23.75"
Tile Tolerance	(+/-0.2") x (+/-0.2")
Thickness	Tiles range from 1" to 5 1/2". Refer to Data Sheet for specific thickness values.
Depth Tolerance	(+/-0.2")
Weight	1680 gsm

Physical Description/ Properties

Boiling Point:	N/A
Melting Point:	482°F
Vapor Pressure:	N/A
Specific Gravity:	Polyester 1.38
Flash Point:	N/A
Explosive Limits:	N/A
Solubility in Water:	Not soluble
Alkalinity:	pH 7.8
Relative Vapor Density:	N/A

Acoustic Performance

3D Ceiling Tiles are specifically designed to reduce and control reverberated noise and echo in building interiors.

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
3D Ceiling Tiles	0.15	0.45	0.65	0.90	0.90	0.80	0.75
3D Ceiling Tiles S-5.37"	0.15	0.65	0.60	0.70	0.75	0.70	0.65



Service

For further information about 3D Ceiling Tiles or any other product, please contact your account manager or visit momentumco.com.

Care and Maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

Product Specifications

Composition

100% polyester fiber from polyethylene terephthalate (PET). 3D Ceiling Tiles contain a minimum of 49% recycled polyester fiber.

Suitable Applications

Decorative and functional acoustic tile for retail, education, hospitality and commercial interiors.

Fire Ratings

3D Ceiling Tiles have been evaluated using the following test methods:

ASTM E-84-14

Class A, FS:0 - SD:10
Report RJ3297

VOC Emissions

Autex Acoustics polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product.
VOC concentration:
0.009 mg/m³ (7 days).

Water Vapor Sorption

ASTM C1104 / C1104M-13a
Test conditions: 49°C, 95%RH
Water vapor absorbed and adsorped after 4 days:
0.4% by weight.

Microbial Resistance

ASTM G21-15
Growth rating: 0 (No growth)
3D Ceiling Tiles do not promote the growth of molds and mildew.

Color Fastness to Light

3D Ceiling Tiles are suitable for indoor use only. Lightfastness is dependent on use and exposure. 3D Ceiling Tiles have been evaluated to the following standard:
ISO 105-B02:2014
Rating: 6 (Highest = 7)

Color Fastness to Rubbing

ISO 105-X12:2016
Dry rating: 4-5 (Highest = 5)
Wet rating: 4-5 (Highest = 5)

Pattern Repeat

Non-woven. No pattern repeat, but the product has a directional grain. Product may vary from samples and batch to batch due to fiber blending and lay-up, which is an inherent feature of this product.

Fabric Care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and using excessive amounts of water as this will affect the finish.

Use carpet or upholstery shampoo as directed. Blot with a clean, dry cloth after each application of the solution.

Custom printed 3D Ceiling Tiles require the services of a specialist cleaning company. Refer to the Autex Acoustics Care and Maintenance Guide for more information.

Autex Acoustics®

M O M E N T U M

momentumco.com

Instagram LinkedIn Pinterest