

ACOUSTIC ABSORPTION BLANKET

GreenStuf® Acoustic Absorption Blanket (AAB™) is a range of **100% polyester acoustic insulation products designed for reducing and controlling reverberated noise in building interiors. GreenStuf AAB is ideally suited for use as an absorber behind acoustic panels and ceiling systems.**

GreenStuf AAB is available in a range of densities and performance options. GreenStuf AAB is supplied as lofted white or black insulation panels /sheets measuring 2400mm x 1200mm.

APPLICATIONS

GreenStuf AAB has been engineered to maximize sound absorption for the control of reverberated noise in building interiors. GreenStuf AAB is ideal for managing noise in theatres, studios, auditoriums, halls, offices, retail and indoor swimming pool complexes. GreenStuf AAB can also be used in marine applications, as acoustic baffles, acoustic infill for silencers and louvres, and insulation for Original Equipment Manufacturers (OEM).

To ensure New Zealand Building Code (NZBC) compliance, architects and building designers are advised to consult an engineer or the relevant NZ standards before specifying acoustic insulation products. For information and assistance please contact your GreenStuf account manager.

TECHNICAL

NZBC Compliance: When installed in accordance with the manufacturer's instructions will satisfy the 50 year durability clause NZBC B2.3.1 (a). GreenStuf meets the relevant clauses of NZBC E3 Internal Moisture, F2 Hazardous Building Materials, and may contribute to meeting H1 Energy Efficiency, and G6 Acoustic Design requirements.

Vermin: GreenStuf is naturally resistant to insect and vermin attack.

Fire Regulations: Greenstuf insulation may not be suitable for all applications, as stipulated in the NZBC.

Please consult a fire engineer when specifying GreenStuf insulation or contact your GreenStuf account manager for further information.

Durability: GreenStuf has a 50 Year Durability Warranty.

Product Format: GreenStuf AAB is available as standard 2400mm x 1200mm sheets, in black and white. Custom sizes, grey colour blends and self-adhesive backed options are available with minimum order quantities on request.

Moisture: GreenStuf is not affected by moisture. Exposure to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption by weight of less than 0.03%.

Hazardous Building Materials: GreenStuf is non-hazardous.

VOC Emission Safe:

VOC concentration: 0.01 mg/m³ (7 days).
GECA/GreenGuard Limit: 0.25 mg/m³ (7 days).
Cetec Pty Ltd (Report: RCV080408)

Non-Corrosive: GreenStuf polyester is considered non-corrosive based on AS/NZS 4859.1 Standard for insulation.

Non-Toxic, Non-Allergenic, Non-Irritant: There are no known hazards with the use or handling of GreenStuf polyester.

MSDS: Material Safety Data Sheets (MSDS) are available on request from your GreenStuf account manager or can be downloaded from our website: www.greenstuf.co.nz

Installation: GreenStuf AAB should ideally be installed with the textured/patterned surface exposed to the sound source. GreenStuf AAB can be fixed to wall and ceiling substrates using a contact type adhesive (ADOS F2) and/or mechanical fixings such as insulation anchors. Additional information and advice are available from your GreenStuf account manager or by visiting our website: www.greenstuf.co.nz

Fire ratings:

ISO 9705: 1993
Classification: Group 1-S
Smoke Production Rate: <5.0m²/s
As required by NZBC C/VM2
FI 4973 and FAR 4045

IEC 60695-11-5 (Downlight Fire Test Standard)
GreenStuf AAB range has been tested and assessed as complying with IEC 60695-11-5 Needle-flame Test.

Specification & Substitution: GreenStuf specification documents are available through Masterspec or can be downloaded from our website: www.greenstuf.co.nz



NAME	DENSITY	THICKNESS	WIDTH	FORM	WEIGHT
Acoustic Absorption Blanket (AAB) 14-25	14kg/m3	25mm	1200mm	Roll Form	350gsm
Acoustic Absorption Blanket (AAB) 25-25	25kg/m3	25mm	1200mm	Slab	625gsm
Acoustic Absorption Blanket (AAB) 35-25	35kg/m3	25mm	1200mm	Slab	875gsm
Acoustic Absorption Blanket (AAB) 48-25	48kg/m3	25mm	1200mm	Slab	1200gsm
Acoustic Absorption Blanket (AAB) 14-50	14kg/m3	50mm	1200mm	Slab	700gsm
Acoustic Absorption Blanket (AAB) 35-50	35kg/m3	50mm	1200mm	Slab	1750gsm
Acoustic Absorption Blanket (AAB) 48-50	48kg/m3	50mm	1200mm	Slab	2400gsm
Acoustic Absorption Blanket (AAB) 20-75	20kg/m3	75mm	1200mm	Slab	1500gsm
Acoustic Absorption Blanket (AAB) 35-75	35kg/m3	75mm	1200mm	Slab	2625gsm
Acoustic Absorption Blanket (AAB) 48-75	48kg/m3	75mm	1200mm	Slab	3600gsm
Acoustic Absorption Blanket (AAB) 20-100	20kg/m3	100mm	1200mm	Slab	2000gsm
Acoustic Absorption Blanket (AAB) 40-100	40kg/m3	100mm	1200mm	Slab	4000gsm
Acoustic Absorption Blanket (AAB) 48-100	48kg/m3	100mm	1200mm	Slab	4800gsm

The performance and design of GreenStuf AAB has been engineered to supply a tested and proven sound control system. Substitution of any specified components in a sound control system can significantly compromise the system performance. Accept NO substitutions.

Manufacture: GreenStuf AAB is manufactured to a strict set of tolerances and best practice. GreenStuf AAB is an acoustic insulation designed to be installed in commercial buildings at height, therefore may contain some fibre colour contamination and/or belt marks. These elements are a result of the manufacturing process, if you require a perfect finished surface please consider our Quietspace® Panel range or consult with your GreenStuf account manager.

Acoustic and Thermal Performance: All GreenStuf AAB acoustic and thermal performance testing has been carried out in a laboratory environment. On-site results could vary depending on the system design, product handling and quality of the installation. For service and advice, please contact your GreenStuf account manager or visit our website: www.greenstuf.co.nz

ISO Standards: GreenStuf is committed to Quality and Environmental best practice through our ISO 9001 & ISO 14001 certified Quality and Environmental Management Systems.

Take Back Programme: GreenStuf is recyclable. GreenStuf will gladly recycle used, uncontaminated GreenStuf insulation to help keep it out of landfills. For more information on recycling GreenStuf contact GreenStuf on freephone 0800 428 839.

Packaging Recycling: GreenStuf packaging is recyclable LDPE 4. Please refer to your local recycling centres for drop off and collection services.

Environmental: All GreenStuf products are manufactured using 100% polyester fibre and contain a minimum of 50% previously recycled fibre (from PET plastic). GreenStuf products are manufactured under GreenStuf's Zero Waste Programme where all manufacturing waste is recycled back into the production process.

GreenStuf products are Global GreenTag GreenRate Level A certified and can be used to contribute to Green Star and Homestar accreditation. GreenStuf is also Declare certified to be Red List chemical free and can be used in Living Building Challenge projects. For more information, please contact your GreenStuf account manager, or visit our website www.greenstuf.co.nz

NAME	DENSITY	THICKNESS	WEIGHT	SOUND ABSORPTION – FREQUENCY						NRC
				125	250	500	1000	2000	4000	
AAB 14-25	14kg/m3	25mm	350gsm	0.13Hz	0.29Hz	0.48Hz	0.62Hz	0.69Hz	0.65Hz	0.50Hz
AAB 25-25	25kg/m3	25mm	625gsm	0.15Hz	0.30Hz	0.50Hz	0.65Hz	0.75Hz	0.75Hz	0.55Hz
AAB 35-2	35kg/m3	25mm	875gsm	0.10Hz	0.38Hz	0.64Hz	0.83Hz	0.88Hz	0.84Hz	0.70Hz
AAB 48-25	48kg/m3	25mm	1200gsm	0.15Hz	0.42Hz	0.73Hz	0.92Hz	0.96Hz	0.90Hz	0.75Hz
AAB 14-50	14kg/m3	50mm	700gsm	0.29Hz	0.54Hz	0.78Hz	0.82Hz	0.80Hz	0.76Hz	0.75Hz
AAB 35-50	35kg/m3	50mm	1750gsm	0.29Hz	0.68Hz	1.01Hz	1.01Hz	0.97Hz	0.95Hz	0.90Hz
AAB 48-50	48kg/m3	50mm	2400gsm	0.21Hz	0.54Hz	0.96Hz	1.08Hz	1.02Hz	1.03Hz	0.90Hz
AAB 20-75	20kg/m3	75mm	1500gsm	0.35Hz	0.60Hz	0.85Hz	0.95Hz	0.90Hz	0.95Hz	0.85Hz
AAB 35-75	35kg/m3	75mm	2625gsm	0.38Hz	0.95Hz	1.16Hz	1.07Hz	0.98Hz	0.96Hz	1.05Hz
AAB 48-75	48kg/m3	75mm	3600gsm	0.40Hz	0.80Hz	1.15Hz	1.10Hz	1.05Hz	1.05Hz	1.05Hz
AAB 20-100	20kg/m3	100mm	2000gsm	0.50Hz	0.85Hz	1.00Hz	0.95Hz	0.95Hz	1.00Hz	0.95Hz
AAB 40-100	40kg/m3	100mm	4000gsm	0.45Hz	1.05Hz	1.15Hz	1.05Hz	1.05Hz	1.05Hz	1.05Hz
AAB 48-100	28kg/m3	100mm	4800gsm	0.88Hz	1.14Hz	1.10Hz	1.03Hz	1.03Hz	0.98Hz	1.10Hz



AN ISO 9001 AND ISO 14001 CERTIFIED COMPANY

GreenStuf® FACTORY AND COLLECTIONS

40 Westpoint Drive,
Hobsonville, Auckland 0618,
New Zealand

FREEPHONE **0800 428 839**

PHONE **+64 9 828 9179**

FAX **+64 9 828 5810**

WEB **greenstuf.co.nz**

The brand names and logos mentioned herein are registered or unregistered trademarks either owned or used under license by Autex Industries Limited or other members of the Autex Group. The contents of this document are protected by Copyright 2024 Autex Industries Ltd. All Rights Reserved.

It is the user's responsibility to determine if the product and information presented in this document are suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your GreenStuf® account manager.