



Autex
Acoustics®

Verve™ Contoured Panels

Manufacturer's Guarantee

Verve™ Contoured Panels are manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

Specification

Product Name	Verve™ Contoured Panels	
Description	100% polyester lightweight semi-rigid panel	
	Metric	
Panel dimensions	2680 mm x 1170 mm	
Tolerance	(+/- 1 mm) x (+/- 1 mm)	
Thickness	12 mm	21 mm
Tolerance	(+/- 6%)	(+/- 6%)
Weight	2400 gsm	3600 gsm

Physical description/
properties

Boiling point	N/A
Melting point	250°C
Vapour pressure	N/A
Specific gravity	Polyester 1.38
Flash point	N/A
Explosive limits	N/A
Solubility in water	Not soluble
Alkalinity	pH 7.8
Relative vapour density	N/A

Acoustic performance

Verve is specifically designed to reduce and control reverberated and echo noise in building interiors.

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
12 mm Verve	0.00	0.05	0.10	0.40	0.70	0.80	0.30
12 mm Verve (with 25 mm air gap)	0.10	0.20	0.50	0.85	0.95	0.85	0.65
21 mm Verve	0.05	0.20	0.55	0.90	1.00	0.90	0.65
21 mm Verve (with 25 mm air gap)	0.15	0.40	0.80	1.00	0.95	0.90	0.80



Product specifications

Composition

100% polyester fibre from polyethylene terephthalate (PET). Verve contains a minimum of 80% previously recycled polyester.

Suitable applications

Partitions, wallcovering with acoustic properties.

Fire Ratings

Verve is made from Cube™ as the base material. Cube has been evaluated using the following test methods.

ISO 9705: 1993

Classification: Group 1-S
Smoke production rate:
<5.0m²/s

As required by NZBC C/VM²

AS ISO 9705 - 2003

Classification: Group 1
(SMOGR_{ARC}): <100m²/s²
AS ISO 9705 - 2003
Classification: Group 1
(SMOGR_{ARC}): <100m²/s²
Assessed using methodology AS ISO 9705 - 2003 in accordance with AS 5637:2015, as required by NCC Specification 7: Fire Hazard properties: S7C4 FI 4974
FAR 4055 Wall applications

BS EN 13501-1:2018

Wall applications
Classification: B-s2,d0
(Cube™ 12 mm)
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011. EUI-20-000268-A

Ceiling applications

Classification: B-s2,d0
(Cube™ 12 mm)
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014. EUI-20-000268-B

Wall applications

Classification: B-s2,d0
(Cube™ 24 mm)
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011. 7191343095-MEC24/03-JV

Ceiling applications

Classification: B-s2,d0
(Cube™ 24 mm)
Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014. 7191343095-MEC24/03-JV

ASTM E-84-15a

Class A, FS:0 - SD:45
(Cube 1/2")
RJ4479-2
Class A, FS:0 - SD:65
(Cube 1")
RJ4479-1

VOC emissions

Autex Acoustics polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product.
VOC concentration:
0.009 mg/m³ (7 days)

Water vapour sorption

ASTM C1104 / C1104M-13a
Test conditions: 49°C, 95%RH
Water vapour absorbed and adsorped after 4 days:
0.4% by weight

Impact resistance

ISO 7892:1988

Hard body impact

There is no surface damage or penetration to Verve when subjected to hard body impacts. When adhered to 10 mm plasterboard, the system can resist a 9 joule impact. This is equivalent to the impact of a 0.5 kg object dropped from a 2 m height. A small indentation might be observed when subjected to an impact equivalent to the impact of a 0.5 kg object dropped from a 0.5 m height.

Soft body impact

There is no surface damage or penetration to Verve when subjected to soft body impacts. When adhered to 10 mm plasterboard, the system can resist a 70 joule impact. This is equivalent to the impact of a 50 kg object dropped from a 150 mm height.

Microbial resistance

ASTM G21-15
Growth rating: 0 (No growth)
Cube does not promote the growth of moulds and mildew.

Colour fastness to light

Verve is suitable for indoor use only. Light fastness is dependent on use and exposure. Verve has been evaluated to the following standard: ISO 105-B02:2014
Rating: 6 (Highest = 7)

Colour fastness to rubbing

ISO 105-X12:2016
Dry rating: 4-5 (Highest = 5)
Wet rating: 4-5 (Highest = 5)

Pattern repeat

Selected designs have a pattern repeat, all designs have a directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up, which is an inherent feature of this product.

Fabric care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution. Custom printed Verve requires the services of a specialist cleaning company. Refer to the Autex Acoustics Care and Maintenance Guide for more information.

● Australia

VIC, TAS, SA
285 Swan St
Richmond
VIC 3121
Phone 03 9450 6700
Freephone 1800 678 160

NSW, ACT
Suite 8.03,
89 York Street,
Sydney 2000
Phone 02 9729 6100

QLD, NT
68 Business St
Yatala
QLD 4207
Phone 07 3001 3000

WA
28 Milly Court
Malaga
WA 6090
Phone 08 9355 1911

Customer Service 1800 678 160 autexacoustics.com.au

Autex Acoustics® products are carbon neutral and contribute to WELL, LEED, Green Star & BREEAM certification. Contact your Autex Acoustics® specification manager to hear how we can support your low carbon goals.

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), & Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited. It's the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitable qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex Acoustics specifications manager. © Copyright 2024 Autex Industries Ltd. All Rights Reserved.