



## Safety Data Sheet

According to OSHA Communication Standard, 29 CFR 1910.1200

Rapid Set TiltWallFixx Textured

### SECTION 1: Identification

#### Product identifier

**Product name:** TiltWallFixx Textured

**Product code:** 703410050

#### Recommended use of the product and restriction on use

**Relevant identified uses:** Commercial use for concrete repair applications.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

United States

CTS Cement Manufacturing Corporation

12442 Knott St.

Garden Grove, CA 92841

800-929-3030

info@ctsceement.com

#### Emergency telephone number:

United States

INFOTRAC 1-800-535-5053

International

INFOTRAC 1-352-323-3500

### SECTION 2: Hazard(s) identification

#### GHS classification:

Skin sensitivity, category 1B

Serious eye damage, category 1

Specific target organ toxicity single exposure, category 3

Specific target organ toxicity repeated exposure, category 1

Carcinogenicity, category 1A

#### Label elements

##### Hazard Pictograms:



**Signal word:** Danger

#### Hazard statements:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured**

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

**Precautionary statements:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

P284 Wear respiratory protection.

P321 Specific treatment (see supplemental first aid instructions on this label).

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P308+P313 If exposed or concerned: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338+P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P312 Call a poison center or doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P402 Store in a dry place.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Hazards not otherwise classified:**

None.

**SECTION 3: Composition/information on ingredients**

Identification	Name	Weight %
CAS number: 65997-15-1	Portland cement	10-40
CAS number: 14808-60-7	Silica, crystalline quartz	30-60



## Safety Data Sheet

According to OSHA Communication Standard, 29 CFR 1910.1200

### Rapid Set TiltWallFixx Textured

Identification	Name	Weight %
CAS number: 1317-65-3	Calcium carbonate	20-40

#### Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

\*Cement is primarily comprised of calcium compounds with oxides of aluminum, iron, sulfur, and silica. Trace amounts of naturally occurring, potentially harmful chemicals might be detected during chemical analysis.

Trace constituents may include, but are not limited to, magnesium, potassium, sodium oxides, and hexavalent chromium.

### SECTION 4: First aid measures

#### Description of first aid measures

##### General notes:

If exposed or concerned: Call a poison center or doctor.

##### After inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If exposed or concerned: Call a poison center or doctor.

##### After skin contact:

Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.

##### After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

##### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If exposed or concerned: Call a poison center or doctor.

#### Most important symptoms and effects, both acute and delayed

##### Acute symptoms and effects:

**SKIN CONTACT:** Exposure may cause irritation. Symptoms include redness, itching, burning and inflammation. Exposure to wet material may cause severe skin burns and irreversible tissue damage. May cause an allergic skin reaction from trace amounts of sensitizing metals in lime.

**EYE CONTACT:** Exposure may cause serious eye damage. Symptoms include irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

**INHALATION:** Inhalation of dust may irritate the nose, throat and respiratory tract. Symptoms include cough, sore throat, shortness of breath and inflammation of the mucous membranes lining the respiratory tract.

**INGESTION:** Ingestion is an improbable route of exposure. Ingestion of wet material would cause corrosive burns to mouth, esophagus and stomach. Symptoms include pain, tissue damage, nausea, diarrhea, and vomiting. If aspiration into the lungs occurs during vomiting, severe lung damage may result.

##### Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure to respirable silica may cause cancer and damage to organs. Prolonged and/or repeated exposure to silica-containing dust may cause lung damage and a lung disease called silicosis. Silicosis is a progressive and



## Safety Data Sheet

According to OSHA Communication Standard, 29 CFR 1910.1200

### Rapid Set TiltWallFixx Textured

disabling lung disease that causes pulmonary fibrosis, chronic obstructive pulmonary disorder (COPD) and lung cancer. Silicosis lowers the immune system and makes an individual more susceptible to tuberculosis. Silicosis may also cause renal disease and scleroderma - a disease affecting skin, blood vessels, joints and skeletal muscles. Symptoms of silicosis may include (but are not limited to) shortness of breath, difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure. Not all individuals with silicosis will exhibit symptoms of the disease. However, silicosis can be progressive, and symptoms can appear at any time, even years after exposures have ceased.

#### Immediate medical attention and special treatment

##### Specific treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued. Exposure to wet material requires prompt medical treatment.

##### Notes for the doctor:

Treat symptomatically.

### SECTION 5: Firefighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition.

##### Unsuitable extinguishing media:

Not determined or not applicable.

##### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors.

##### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

##### Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion. Heating causes a rise in pressure, risk of bursting and combustion.

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation. Ensure air handling systems are operational. Wear protective eyewear, gloves, and clothing.

#### Environmental precautions:

Should not be released into the environment. Prevent from reaching drains, sewer or waterway.

#### Methods and material for containment and cleaning up:

Wear protective eyewear, gloves and clothing. Sweep or scoop up solid material while minimizing dust generation. Dispose of contents/container in accordance with local regulations.

#### Reference to other sections:

Not determined or not applicable.

### SECTION 7: Handling and storage

#### Precautions for safe handling:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured**

Do not breathe dust, mist, vapors, or spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Do not eat, drink, smoke or use personal products when handling chemical substances.

**Conditions for safe storage, including any incompatibilities:**

Keep container tightly sealed. Keep container dry. Store locked up. Store in a cool, well-ventilated area.

**SECTION 8: Exposure controls/personal protection**

Only those substances with limit values have been included below.

**Occupational Exposure limit values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Portland cement	65997-15-1	ACGIH TLV TWA 1 mg/m <sup>3</sup>
	Calcium carbonate	1317-65-3	10 mg/mg <sup>3</sup> total dust, 3 mg/m <sup>3</sup> respirable dust
	Total silica, crystalline quartz	14808-60-7	ACGIH TLV TWA 0.025000 mg/m <sup>3</sup>
United States (OSHA)	Portland cement	65997-15-1	OSHA 8 hr TWA PEL: 15 mg/m <sup>3</sup> (total dust), 5 mg/m <sup>3</sup> (respirable fraction)
	Calcium carbonate	1317-65-3	TWA 5 mg/m <sup>3</sup> (respirable fraction), 15 mg/m <sup>3</sup> (total dust)
	Silica, crystalline quartz (Respirable)	14808-60-7	OSHA 8-hour TWA PEL: 0.025
	mg/m <sup>3</sup> (Respirable fraction, action level)	14808-60-7	TWA 0.050000 mg/m <sup>3</sup> USA. NIOSH
	Silica, crystalline quartz (Respirable)	14808-60-7	OSHA 8-hour TWA PEL: 0.05
	mg/m <sup>3</sup> (Respirable fraction, exposure limit level)		
NIOSH	Portland cement clinker	65997-15-1	NIOSH TWA 10 mg/m <sup>3</sup> (total dust), 5 mg/m <sup>3</sup> (respirable fraction)
	Silica, crystalline quartz (Respirable)	14808-60-7	NIOSH TWA 0.05 mg/m <sup>3</sup>

**Biological limit values:**

No biological exposure limits noted for the ingredient(s).

**Information on monitoring procedures:**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

**Appropriate engineering controls:**

Emergency eyewash fountains and safety showers should be available in the immediate vicinity of use or handling. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

**Personal protection equipment**

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured****Eye and face protection:**

Safety goggles or glasses, or appropriate eye protection.

**Skin and body protection:**

Select glove material impermeable and resistant to the substance. Wear appropriate clothing to prevent any possibility of skin contact.

**Respiratory protection:**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

**General hygienic measures:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, mist, vapors, or spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Do not eat, drink, smoke or use personal products when handling chemical substances.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties**

Appearance	Solid; Gray powder
Odor	Low
Odor threshold	Not available
pH	11 - 12 when wet
Melting point/freezing point	Not available
Initial boiling point/range	>1000°C (1832°F)
Flash point (closed cup)	Not available
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Density	Not available
Relative density	2.7 - 3.1
Solubilities	Partially soluble
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	Not available
Dynamic viscosity	Not applicable
Kinematic viscosity	Not applicable



## Safety Data Sheet

According to OSHA Communication Standard, 29 CFR 1910.1200

### Rapid Set TiltWallFixx Textured

Explosive properties	Not available
----------------------	---------------

Oxidizing properties	Not available
----------------------	---------------

#### Other information

VOC (Weight %)	0 g/l when mixed with water
----------------	-----------------------------

### SECTION 10: Stability and reactivity

#### Reactivity:

Does not react under normal conditions of use and storage.

#### Chemical stability:

Stable under normal conditions of use and storage.

#### Possibility of hazardous reactions:

Hazard polymerization will not occur.

#### Conditions to avoid:

Avoid dust formation.

#### Incompatible materials:

Strong acids, strong bases, strong oxidizers. Dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas.

#### Hazardous decomposition products:

Ash may contain trace amounts of ammonia. When exposed to water or used in combination with Portland cement, some ash sources may outgas ammonia. Thermal decomposition may produce silicon oxides.

### SECTION 11: Toxicological information

#### Information on toxicological effects:

##### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data is available.

**Substance data:** No data is available.

##### Skin corrosion/irritation

**Assessment:** Causes skin irritation. May cause caustic burns when in prolonged contact with skin. Irritating or corrosive to mouth, throat, and gastrointestinal tract.

**Product data:** No data is available.

**Substance data:** No data is available.

##### Serious eye damage/irritation

**Assessment:** Causes serious eye damage and possible blindness. Damage may be permanent if treatment is not immediate. Additionally, may cause temporary irritation through mechanical abrasion.

**Product data:** No data is available.

**Substance data:** No data is available.

##### Respiratory or skin sensitization

**Assessment:** Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation of crystalline silica may cause other adverse

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured**

effects including lung and kidney cancer. Product may contain trace concentrations (<0.1%) of chromate and nickel compounds that can cause an allergic skin reaction. Further skin contact may result in inflammation, rash, and itching.

**Product data:** No data is available.

**Substance data:** No data is available.

**Carcinogenicity**

**Assessment:** May cause cancer.

**Product data:** No data is available.

**Substance data:**

Name	Species	Result
Silica, crystalline quartz (Respirable)	Not applicable	Component may cause cancer.
Total Silica, crystalline quartz		1 - Group 1: Carcinogenic to humans (Quartz)

**International Agency for Research on Cancer (IARC):**

Name	Classification
Silica, crystalline quartz (Respirable)	Group 1 - Carcinogenic to human

**National Toxicology Program (NTP):**

Name	Classification
Silica, crystalline quartz (Respirable)	Known to be human carcinogens

**Germ cell mutagenicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data is available.

**Substance data:** No data is available.

**Reproductive toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data is available.

**Substance data:** No data is available.

**Specific target organ toxicity (single exposure)**

**Assessment:** May cause respiratory irritation by breathing dust. Inflammation of the respiratory passages, ulceration and perforation of the nasal septum and pneumonia has been attributed to inhalation of dust.

**Product data:** No data is available.

**Substance data:** No data is available.

**Specific target organ toxicity (repeated exposure)**

**Assessment:** May cause damage to organs (lungs) through prolonged or repeated exposure. The extent and severity of lung injury correlates with the length of exposure and dust concentration. Inflammation of the respiratory passages, ulceration and perforation of the nasal septum and pneumonia has been attributed to the inhalation of dust containing calcium oxide. Product contains crystalline silica. Long term exposure to fine airborne crystalline silica dust may cause silicosis a form of pulmonary fibrosis that can cause shortness of breath, cough, and reduced lung function. Particles with diameters less than 1 micrometer are considered most hazardous.

**Product data:** No data is available.

**Substance data:** No data is available.

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured****Aspiration toxicity****Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data is available.**Substance data:** No data is available.**Information on likely routes of exposure:**

Eye and skin contact, inhalation.

**Symptoms related to the physical, chemical and toxicological characteristics:**

No data is available.

**Other information:**

No data is available.

**SECTION 12: Ecological information****Acute and chronic toxicity****Assessment:** Based on available data, the classification criteria are not met.**Product data:** No data available.**Substance data:** No data available.

Calcium carbonate

WGK Classification (AwSV) 317 WGK: nwg

Crystalline Silica quartz

WGK Classification (AwSV) 849 WGK: nwg

**Persistence and degradability****Product data:** No data available.**Substance data:** No data available.**Bioaccumulative potential****Product data:** No data available.**Substance data:** No data available.**Mobility in soil****Product data:** No data available.**Substance data:** No data available.**Other adverse effects:** No data available.**SECTION 13: Disposal considerations****Disposal methods:**

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities. Dispose of contents/container in accordance with local, regional, national, and international regulations.

**SECTION 14: Transport information****United States Transportation of dangerous goods (49 CFR DOT)**

UN number	Not regulated
UN proper shipping name	Not regulated

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured**

UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

**International Maritime Dangerous Goods (IMDG)**

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

**International Air Transport Association Dangerous Goods Regulations (IATA-DGR)**

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

**SECTION 15: Regulatory information**

**United States regulations Inventory listing (TSCA):** Substances are listed on the TSCA inventory or are exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

**SARA Section 311/312 hazard classes:** Ash, health hazard: Specific target organ toxicity (single or repeated exposure); health hazard: Carcinogenicity; health hazard: Serious eye damage or eye irritation.

**SARA Section 313 toxic chemicals:** None of the ingredients are listed.

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
1317-65-3	Calcium carbonate	Listed

**New Jersey Right to Know:**

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured**

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
1317-65-3	Calcium carbonate	Listed

**New York Right to Know:**

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
1317-65-3	Calcium carbonate	Listed

**Pennsylvania Right to Know:**

14808-60-7	Silica, crystalline quartz (Respirable)	Listed
1317-65-3	Calcium carbonate	Listed

**California Proposition 65:**

**L WARNING:** Can expose you to crystalline silica\*, a carcinogen, and hexavalent chromium, a reproductive toxicant. See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**SECTION 16: Other information****Abbreviations and Acronyms:**

**ACGIH:** American Conference of Governmental Industrial Hygienists  
**ADR:** European Road Transport  
**AU:** Australia  
**CA:** Canada  
**CAS:** Chemical Abstracts Service  
**CERCLA:** Comprehensive Environmental Response, Compensation, and Liability Act  
**CN:** China  
**CPR:** Controlled Products Regulations  
**DFG:** Deutsche Forschungsgemeinschaft  
**DOT:** Department of Transportation  
**DSL:** Domestic Substances List  
**EEC:** European Economic Community  
**ECHA:** European Chemicals Agency  
**EINECS:** European Inventory of Existing Commercial Chemical Substances  
**EPA:** Environmental Protection Agency  
**EU:** European Association  
**IARC:** International Agency for Reach on Cancer  
**IMDG:** International maritime dangerous goods code  
**IATA:** International Air Transport Association  
**ICAO:** International Civil Aviation Organization  
**JP:** Japan  
**COD:** Chemical Oxygen Demand  
**BOD5:** 5-day biochemical oxygen demand  
**BCF:** Bioconcentration factor  
**LD50:** Lethal Dose 50  
**CL50:** Lethal Concentration 50

**Safety Data Sheet**

According to OSHA Communication Standard, 29 CFR 1910.1200

**Rapid Set TiltWallFixx Textured****EC50:** Effective concentration 50**Log-POW:** Octanol-water partition coefficient**Koc:** Partition coefficient of organic carbon**Know:** Octanol/water partition coefficient**KR:** Korea**LEL:** Lower Explosive Limit**UEL:** Upper Explosive Limit**NIOSH:** National Institute for Occupational Safety and Health Administration**PH:** Philippines**RCRA:** Resource Conservation and Recovery Act**OSHA:** Occupational Safety and Health Administration**RID:** European Rail Transport**SARA:** Superfund Amendments and Reauthorization Act**STEL:** Short Term Exposure Limit**TDG:** Transportation of Dangerous Goods**TSCA:** Toxic Substances Control Act**TWA:** Time Weighted Average**US:** United States**Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 3-0-0**HMIS:** 3\*-0-0**Initial preparation date:** 12/14/23**Version #:** 2**Revision Date:** 10/10/25**End of Safety Data Sheet**