



Piano Basic – Plus – Plus VRA

CLINICAL AUDIOMETER

DESCRIPTION

Piano is an advanced clinical audiometer with two separate and independent channels. Piano features a complete battery of tests, all easily managed via a wide touch screen color display.

The “Plus VRA” version of the Piano audiometer forms the heart of a professional VRA system and can use as reinforces either traditional cabinet toys or videos and images on one or more displays.

CLASSIFICATION

IEC 60645-1: Type 1 Class A/AE
 ANSI S3.6: Type 1A/1AE
 IEC 60645-1 / ANSI S3.6: EHF (Extended High Frequency) Compliant (Piano Plus / Plus VRA only)

AVAILABLE SIGNALS

Stimulus: pure tone, warble tone
 2 external inputs for speech audiometry
 MIC input for live speech audiometry
 Internal input (flash memory) for speech audiometry
 Masking: NBN, WN, SN

SIGNALS SPECIFICATION

Attenuator step: 1 and 5 dB
 Presentation: Continuous, Pulsed (0.5, 1 and 2 Hz or custom freq.), Single Pulse (with selectable duration)
 Warble: 5 Hz sin wave modulating signal

AVAILABLE OUTPUTS AND TRANSDUCERS

AC: TDH-39 or DD45 headphones, ER-3 insert earphones, HDA-300 headphones (Piano Plus / Plus VRA only)
 BC: B-71 bone vibrator
 Free field
 Insert masking earphone: IME-100

AVAILABLE TESTS

- Pure Tone audiometry
- Auto threshold (modified Hughson-Westlake)
- Speech audiometry (2 channels)
- ABLB
- MLB
- SISI: automatic score; 1 dB increment (5 dB for familiarization)
- DLI, with increments between 0 and 5 dB
- Tone decay, with 60 or 120 sec. duration
- Stenger, with pure tone or speech stimulation
- 2 independent channels Master Hearing Aid
- TEN test
- QuickSIN® test (optional)

Only on Piano Plus:

- HF audiometry: from 8 to 20 kHz
- Multi Frequency: frequency steps selectable between 1/3, 1/6, 1/12 and 1/24 octave
- Bekesy Test: 125 Hz to 8 kHz fixed or sweep frequency, continuous or pulsed tone
- Masking Level Difference (MLD): noise and / or signal out of phase

Only on Piano Plus VRA:

- Visual Reinforcement Audiometry (VRA) test
- Conditioned Play Audiometry (CPA) test

PURE TONE: FREQUENCIES AND MAXIMUM LEVELS (dB HL)

| Freq. (Hz) | AC TDH-39 DD45 | AC HDA-200(*) HDA-300 | AC ER-3 | AC ER-5(*) | BC | FF (**) |
|------------|----------------|-----------------------|---------|------------|----|---------|
| 125 | 80 | 85 | 90 | 90 | - | 75 |
| 250 | 100 | 100 | 105 | 100 | 45 | 85 |
| 500 | 120 | 110 | 110 | 110 | 65 | 95 |
| 750 | 120 | 110 | 115 | 120 | 70 | 95 |
| 1.000 | 120 | 110 | 120 | 120 | 75 | 95 |
| 1.500 | 120 | 110 | 120 | 120 | 80 | 95 |
| 2.000 | 120 | 110 | 120 | 115 | 80 | 95 |
| 3.000 | 120 | 110 | 120 | 115 | 75 | 95 |
| 4.000 | 120 | 105 | 110 | 110 | 75 | 95 |
| 6.000 | 110 | 100 | 100 | 100 | 55 | 90 |
| 8.000 | 100 | 90 | 90 | 90 | 50 | 85 |
| 9.000 | - | 90 | - | - | - | 80 |
| 10.000 | - | 90 | - | - | - | 80 |
| 11.200 | - | 90 | - | - | - | 80 |
| 12.500 | - | 80 | - | - | - | 80 |
| 14.000 | - | 70 | - | - | - | 80 |
| 16.000 | - | 50 | - | - | - | 50 |
| 18.000 | - | 110 dB SPL | - | - | - | - |
| 20.000 | - | 110 dB SPL | - | - | - | - |

(*) Transducer supported but no more available for purchasing
 (**) The values refer to “normal” range; add 10 dB to each value in case of “extended range” option selected

SPEECH AUDIOMETRY: MAXIMUM LEVELS (dB HL)

| AC (*) TDH-39 DD45 | AC HDA-200 HDA-300 | AC ER-3 | AC ER-5 | BC | FF |
|--------------------|--------------------|---------|---------|----|----------------------------|
| 100 | 90 | 100 | 100 | 60 | Normal: 75 Extended: 85 |

(*) Reduce by 20dB in case of free field equivalent filter activation.

PATIENT –OPERATOR COMMUNICATION

Talk over: built-in or external microphone
 Talk back: through built-in speaker or monitor headset (included); clip-on patient microphone included
 Up to 2 patient response buttons (left and right)

MONITOR SIGNAL

Both channels and patient voice monitored through the built-in speaker or monitor headset (included)

ASSISTANT MONITOR

Available only on Piano VRA version:
The Assistant monitor headphone is used for the operator to assistant communication.

PRINTER

Optional integrated thermal printer. Paper size: 112 mm

INTERNAL FLASH MEMORY

Used to store the speech material (.wav format)
Capacity: 4 GB (more than 6 hours of speech)
Speech material upload: through ATIT software (incl.)

CALIBRATION

Validity: 12 months.
All the parameters set through the device software

COMPUTER INTERFACE

Connection: USB (driverless)
Compatible software: Inventis Maestro

HYBRID TECHNOLOGY

Description: Piano can be controlled either as a stand-alone or as a PC-controlled audiometer
It requires Inventis Maestro software.

DISPLAY

Type: Graphical colour TFT LCD. Size: diagonal 7", 150 mm x 90 mm
Resolution: 800 x 480. Resistive touch screen

POWER SUPPLY

External medical grade power supply.
AC consumption: 100-240Vac 47-63Hz 0.9-0.34A
DC output: 6V, 4,16A cont.

MECHANICS

Without integrated printer:
Size (WxDxH): 32 x 32 x 15 cm / 12.6 x 12.6 x 5.9 in
Weight: 2 Kg / 4.4 lbs
With integrated printer:
Size (WxDxH): 32 x 39 x 15 cm / 12.6 x 15.4 x 5.9 in
Weight: 2.5 Kg / 5.5 lbs

FREIGHT PACKING

Size (WxDxH): 47 x 40 x 35 cm / 18.5 x 15.8 x 13.8 in
Gross weight (without printer): 4.4 Kg / 9.7 lbs
Gross weight (with printer): 4.9 Kg / 10.8 lbs

APPLICABLE STANDARDS

Pure tone audiometry: IEC 60645-1, ANSI S3.6
Speech audiometry: IEC 60645-1, ANSI S3.6
High Frequency audiometry: IEC 60645-1, ANSI S3.6
Calibration: ISO 389-1 (TDH 39 and DD45), ISO 389-2 (ER-3 and ER-5), ISO 389-3 (B71), ISO 389-5 (HF), ISO 389-7 (FF), data from the manufacturer (HDA-300 headphones)
Electrical safety: IEC 60601-1, Class I type BF
EMC: IEC 60601-1-2

CE CERTIFICATE

93/42/EEC classification : Class IIa
Classification rule (Annex IX, 93/42/EEC): 10
Notified body: TÜV SÜD Product Service GmbH (0123)

PRODUCT CODES

10147: Piano model Basic – Clinical audiometer
10164: Piano model Basic – Clinical audiometer – with integrated thermal printer
10148: Piano model Plus – Clinical audiometer
10165: Piano model Plus – Clinical audiometer – with integrated thermal printer
10300: Piano model Plus VRA – Clinical audiometer with VRA exam
10306: Piano model Plus VRA - Clinical audiometer with VRA exam - with integrated thermal printer

INCLUDED PARTS

- TDH-39 or DD45 supra-aural headphones
- HDA-300 headphones (Piano Plus / Plus VRA only)
- B71 bone vibrator
- Patient response switch
- Monitor headset with boom microphone
- Clip-on microphone for patient-to-operator communication
- Plastic cover sheet
- Medical grade power supply
- USB connection cable
- User manual
- Desktop response switch for children (Piano Plus VRA only)
- Integrated thermal printer (Printer versions only)

OPTIONAL ACCESSORIES (with order code)

- 10833: ER-3C insert earphones
- 10177: IME-100 insert masking earphone
- 10181: Desktop, battery operated microphone for live speech tests
- 10266: One active speaker FBT J-5A

OTHER OPTIONAL PARTS (with order code)

- 10179: Amplivox Audiocups noise excluding enclosures for TDH-39 / DD45 headphones
- 10180: Cable set for sound booth
- 10182: Soft carrying case
- 10257: Additional patient response switch
- 10293: Thermal paper for Harp and Piano audiometers (box of 5)
- 10533: QuickSIN® test license

Only for Piano Plus VRA:

- 10302: Visual Reinforcement for Piano VRA – Toy Type 1
- 10303: Visual Reinforcement for Piano VRA – Toy Type 2
- 10053: Dedicated table for Pediatric Audiometry systems
- 10307: Stand for toy and speaker
- 10308: Pre-configured mini-tower computer with 4 video outputs - includes the webcam

Piano is developed by Inventis s.r.l.
info@inventis.it
www.inventis.it

The Inventis Quality System complies with ISO 13485 standard.