



Audibel | Technical Data

CROS System

RIC RT & RIC 312

The Audibel CROS System includes products specifically designed for patients who need sound routed to a better hearing ear. The CROS solution transmits sound wirelessly from a microphone placed on a patient's unaidable ear to a receiver fitted on a patient's better hearing ear. Devices can also be configured as a BiCROS solution for patients who need amplification in their better hearing ear.

Vitality AI 24 | 20 | 16

Special Features

- Clear and consistent wireless streaming using 2.4 GHz + NFMI technology
- Telecoil standard in Vitality AI RIC RT CROS receivers
- Compatible with StarLink 2.0 and StarLink Edge accessories

Compatibility

Vitality AI RIC RT CROS is compatible with Vitality AI RIC RT

Vitality AI RIC 312 CROS is compatible with Vitality AI RIC 312

Battery Information

Model	Battery size	IEC code	ANSI code
Vitality AI RIC RT CROS	N/A	N/A	N/A
Vitality AI RIC 312 CROS	312	PR41	7002ZD

Radio Information

Antenna type:	Coil wrapped on ferrite core
Operation frequency:	10.281 MHz NFMI
Occupied bandwidth (99% BW):	400 kHz
Modulation:	8 DPSK
Operating range:	30 cm
Wearing options:	Receiver-In-Canal
Use case:	Streaming of audio signal to receiving hearing aid on the other ear

Audio Information

Audio Quality: 20 kHz sampling frequency

Standards Applied

USA	Canada
RIC RT FCC ID: EOA-24EDGRICRT	RIC RT IC: 6903A-24EDGRICRT
RIC 312 FCC ID: EOA-24EDGR312	RIC 312 IC: 6903A-24EDGR312

General Information

Transportation and storage conditions for the RIC RT and RIC 312:

Your hearing aids should be stored and transported within the temperature, humidity, and pressure ranges of -10°C (14°F) to +45°C (113°F), 10%-95% rH, and 70 kPa – 106 kPa (equivalent to altitudes from 1,200 ft (380 m) below sea level to 10,000 ft (3,000 m)). The charging temperature range is between 10°C (50°F) and 40°C (104°F) and between 10%-95% RH and 70 kPa-106 kPa. Your hearing aids are designed to operate beyond the range of temperatures comfortable to you, from 0°C (32°F) up to 40°C (104°F).

Safety Standards:

Meets IEC 60601-1 and 60601-2-66 safety standards and IEC 60601-1-2 EMC standard.