




Starkey | Technical Data

ITE R

In-The-Ear Rechargeable

Fitting Range

- M
- P



G Series AI 12 | 10

Color Guide

Faceplate Colors



Shell Colors



Patient Features

- IP Rating: 68
- Tinnitus Technology
- Wireless Connectivity
- Rechargeable Battery
- Telecoil
- Compatible with StarLink accessories

	M	P	Matrices: M, P Battery: Lithium-ion
Measurement	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	
Peak OSPL90 (dB SPL)	114	117	
HFA OSPL90 (dB SPL)	109	113	
Peak Gain (dB)	51	58	
HFA Full-On Gain (dB)	46	54	
Frequency Range (Hz)	<100-7600	<100-5700	
HFA Frequencies (kHz)	1.0, 1.6, 2.5	1.0, 1.6, 2.5	
Reference Test Gain (dB)	32	36	
Equivalent Input Noise (dB SPL) <i>Expansion On (Default)</i>	15	15	
Equivalent Input Noise (dB SPL) <i>Expansion Off</i>	25	25	
Harmonic Distortion			
500 Hz (%)	<3	<3	
800 Hz (%)	<3	<3	
1600 Hz (%)	<3	<3	
Induction Coil Sensitivity			
HFA SPLITS (ANSI) (dB SPL)*, **	92	97	
MASL (IEC) (dB SPL)*	74	83	
Estimated Lithium-ion Battery Life***			
Without streaming (hrs)	Up to 42	Up to 42	
With streaming (hrs)	Up to 36	Up to 36	
Battery Current (mA)	0.9	0.9	

* Devices built with a vertical coil orientation.

**HFA SPLITS values could be increased by up to 6 dB for horizontal coil orientation.

***Results will vary based on wireless usage.





Starkey | Technical Data

ITE R

In-The-Ear Rechargeable

G Series AI 12 | 10



Latency (ms)	4.3
Attack Time (ms)	3
Release Time (ms)	60