



Starkey | Technical Data


POWER PLUS

BTE 13

Behind-The-Ear

Fitting Range

● BTE 13 80



Evolv AI

Color Guide

Standard Colors



Accessory Compatibility

- Remote Mic Plus
- Remote Control
- Mini Remote Mic
- Table Microphone
- TV Streamer
- Programmer

Patient Features

- IP Rating: 68
- Tinnitus Technology
- Wireless Connectivity
- Telecoil

Evolv AI Technology

- Healthable monitoring technology with embedded sensors and artificial intelligence

	Earhook	Thin Tube	Matrices: 140/80 Battery Size: 13	
--	---------	-----------	--------------------------------------	--

Measurement	ANSI/IEC 2cc Coupler		ANSI/IEC 2cc Coupler	
	ANSI/IEC 2cc Coupler	IEC OES Coupler	ANSI/IEC 2cc Coupler	IEC OES Coupler
Peak OSPL90 (dB SPL)	140	147	133	139
HFA OSPL90 (dB SPL)	132	N/A	119	N/A
RTF OSPL90 (dB SPL)	N/A	141	N/A	128
Peak Gain (dB)	80	86	78	84
HFA Full-On Gain (dB)	73	N/A	60	N/A
RTF Full-On Gain (dB)	N/A	81	N/A	70



Frequency Range (Hz)	<100-5200	<100-6400	<100-5200	<100-7000
Reference Test Freq. (kHz)	N/A	1.6	N/A	1.6
HFA Frequencies (kHz)	1.0, 1.6, 2.5	N/A	1.0, 1.6, 2.5	N/A
Reference Test Gain (dB)	55	64	44	52
Equivalent Input Noise (dB)	26	26	37	34

Harmonic Distortion				
500 Hz (%)	<5	<5	<1	<1
800 Hz (%)	<2	<1	<1	<2
1600 Hz (%)	<1	<1	<2	<3
3200 Hz (%)	<1	<1	<2	<2

Induction Coil Sensitivity				
HFA SPLITS (ANSI) (dB SPL)	112	N/A	98	N/A
RSETS	-3	N/A	-6	N/A
HFA-SPLIV	114	N/A	100	N/A
RTLS / ETLS	-1	N/A	-4	N/A
HFA MASL (IEC) (dB SPL)	96	N/A	80	N/A
Battery Current (mA)	3.1	2.9	3.1	2.9
Idle Current (mA)	2.1	2.1	2.1	2.1

Estimated Battery Life for 16-Hour Day				
13 Zinc Air (days)	5-8*	7-10*	6-9*	7-10*

Tinnitus Therapy Stimulus				
Max RMS Output (dB SPL)	92		92	
Weighted RMS Output Level (dB SPL)	92		92	
Max 1/3 Octave Output (dB SPL)	92		92	



*Results will vary based on wireless usage.




Starkey | Technical Data

POWER PLUS BTE 13

Behind-The-Ear

Evolv AI



Latency (ms)	4.3
Attack Time (ms)	8
Release Time (ms)	55