




Audibel | Technical Data

CIC

Completely-In-Canal

Fitting Range

- L
- M
- P
- UP



Aris AI 24 | 20 | 16

Color Guide

Faceplate Colors



Shell Colors



Patient Features

- IP Rating: 68
- Tinnitus Technology
- Wireless Connectivity

Aris AI Technology

- Personal health monitoring technology with embedded sensors and artificial intelligence
- Compatible with StarLink 2.0 accessories and StarLink Edge accessories

	L	M	P	UP	Matrices: L, M, P, UP Battery Size: 312
Measurement	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	
Peak OSPL90 (dB SPL)	109	113	117	125	
HFA OSPL90 (dB SPL)	104	109	113	121	
Peak Gain (dB)	42	51	60	67	
HFA Full-On Gain (dB)	36	47	54	63	
Frequency Range (Hz)	<100-9400	<100-8500	<100-6600	<100-5800	
HFA Frequencies (kHz)	1.0, 1.6, 2.5	1.0, 1.6, 2.5	1.0, 1.6, 2.5	1.0, 1.6, 2.5	
Reference Test Gain (dB)	27	32	36	44	
Equivalent Input Noise (dB SPL) Expansion On (Default)	15	15	15	15	
Equivalent Input Noise (dB SPL) Expansion Off	25	25	25	25	
Harmonic Distortion					
500 Hz (%)	<3	<3	<3	<3	
800 Hz (%)	<3	<3	<3	<3	
1600 Hz (%)	<3	<3	<3	<3	
Estimated Battery Life for 16-Hour Day					
Without Streaming (days)	Up to 8	Up to 8	Up to 8	Up to 8	
With Streaming (days)	Up to 7	Up to 7	Up to 7	Up to 7	
Battery Current (mA)	1.3	1.3	1.3	1.4	
Tinnitus Therapy Stimulus					
Max RMS Output (dB SPL)	87	87	87	87	
Weighted RMS Output Level (dB SPL)	87	87	87	87	
Max 1/3 Octave Output (dB SPL)	87	87	87	87	







Audibel | Technical Data

CIC

Completely-In-Canal

Aris AI 24 | 20 | 16



Latency (ms) 4.3

Attack Time (ms) 3

Release Time (ms) 60