

HOW SUPERIOR BULLET PROTECTION SHOULD FEEL

TECH DATA SHEET—KEVLAR[®] EXO[™] XP[®] E480



INTEGRATING KEVLAR[®] EXO[™] WITH XP[®] TECHNOLOGY CAN ENABLE BEST IN CLASS BALLISTICS PROTECTION AND COMFORT

Best-in-class multi-axial structure for soft armor solutions offering superior ballistic protection accompanied by flexibility and comfort advantages over comparable aramid structures.

Learn more by visiting kevlarexo.com

50 YEARS OF KEVLAR[®] LEGACY REBORN IN KEVLAR[®] EXO[™] XP[®]



		WEIGHT	WIDTH	LENGTH	THICKNESS
KEY PRODUCT SPECIFICATIONS	XP [®] E480	14.27 OZ YD ² 484 GM ²	160 CM 63 IN	65 M 71 YD	0.51 MM 0.02 IN

PERFORMANCE ATTRIBUTES

- The exclusive XP[®] multi-axial structure technology can provide unique balance of ballistic and trauma reduction capabilities allowing a minimum of 25% weight reduction
- Allows the construction of flexible and comfortable monolithic design or maximize performance through hybrid solutions at low weights*

EXCEEDING STANDARDS

- Multi-axial structure can provide high stopping power and excellent bullet flattening
- Exceptional durability provided by the unique fiber and 3D structure
- Reduced layer counting and stitching can result in lower manufacturing and labor costs

PROPER STORAGE AND HANDLING

- Keep covered with black, impermeable plastic and avoid crushing, tearing and abrasion
- Do not use bleach or products containing bleach to clean Kevlar[®] EXO[™]
- Avoid exposure to direct sunlight, UV light and temperatures above 66°C (150°F)

*Specifically Ballistic Resistance of Body Armor NIJ Standard-0101.06 and Ballistic Resistance of Body Armor, NIJ Standard 0101.07
This information is based upon technical data that Arclin believes to be reliable. It is subject to revision as additional knowledge and experience become available. It is the user's responsibility to determine the level of toxicity, and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, DUPONT DE NEMOURS, INC. AND ITS AFFILIATES MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS PRODUCT AND INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of Arclin or other persons covering any material or its use. © 2026 Arclin. Arclin and all trademarks denoted with [™] or [®] are owned by Arclin or its affiliates unless otherwise noted.