

## TECTUS

### TE 540 3D

For flush commercial doors

<b>Hinge</b>	<b>up to 120 kg (264 lbs.)</b>
--------------	--------------------------------

#### Product Features

- Completely concealed hinge system
- For wood, steel or aluminum door panels and frames
- For flush commercial doors
- Finger protection due to a small gap between door and frame
- Easily adjustable in three dimensions (side +/- 3.0 mm (0.118"), height +/- 3.0 mm (0.118"), compression +/- 1.0 mm (0.039"))
- Maintenance-free slide bearings
- UL listed for 20 minute fire door

The specification text can be downloaded from the PRODUCTSELECTOR at [www.simonswerk-usa.com](http://www.simonswerk-usa.com).

#### Technical Data

Load capacity	120 kg (264 lbs.)
Length	200 mm (7.874")
Width (door)	32 mm (1.260")
Width (frame)	32 mm (1.260")
Router bit/collar Ø	3/4" / 1"

#### Finishes

satin chrome look (F1) (124), satin nickel look (F2) (125), stainless steel look (SSL) (126), rustic umber (156), bronze metallic (168), traffic white (RAL 9016) (070), matte deep black (RAL9005) (107), polished brass (030), polished nickel (038), satin nickel (144), satin chrome (146), bronze finish light (175), bronze finish (174), bronze finish dark (176), satin brass (047), other finishes available upon request

#### Combinations

Receiver/Reinforcement	Commercial frame	Frame mounted
	Casing frame	TE 540 3D FZ
	Steel frame	TE 540 3D SZ
	Steel door	TE 540 3D ST
	Aluminum frame	Specified by manufacturer

#### Installation Tools

Jig	Universal milling frame	
Step 1	routing template	No. 5 251060 5
Step 2	routing template	No. 5 251061 5

#### Application Range

Fire Resistant, Smoke Resistant, Soundproof, Forced Entry Resistant

#### Note

The load capacity mentioned above refers to the use of 2 hinges per door leaf with a height/width ratio of 2:1 (see page 46 for further detail).  
For a minimum door panel thickness of 40 mm (1-5/8").  
For fire rated doors: Check with door manufacturer regarding the usage of additional required intumescent material.  
Square-corner cover plates are available upon request – see page 34.  
The load capacity may be reduced when installed in combination with a door closer.  
For further information, please contact us.

