

## TECTUS

### TE 240 3D

For flush residential doors

<b>Hinge</b>	<b>up to 60 kg (132 lbs.)</b>
--------------	-------------------------------

#### Product Features

- Completely concealed hinge system
- For wood, steel or aluminum door panels and frames
- For flush residential doors
- Finger protection due to a small gap between door and frame
- Easily adjustable in three dimensions (side +/- 3.0 mm (0.118"), height +/- 3.0 mm (0.118"), compression +/- 1.0 mm (0.039"))
- Maintenance-free slide bearings

The specification text can be downloaded from the PRODUCTSELECTOR at [www.simonswerk-usa.com](http://www.simonswerk-usa.com).

#### Technical Data

Load capacity	60 kg (132 lbs.)
Length	155 mm (6.102")
Width (door)	18 mm (0.709")
Width (frame)	21 mm (0.827")
Router bit / collar Ø	1/2" / 1"

#### Finishes

satin chrome look (F1) (124), satin nickel look (F2) (125), stainless steel look (SSL) (126), rustic umber (156), bronze metallic (168), traffic white (RAL 9016) (070), matte deep black (RAL 9005) (107), polished brass (030), polished nickel (038), satin nickel (144), satin chrome (146), bronze finish light (175), bronze finish (174), bronze finish dark (176), satin brass (047), other finishes available upon request

#### Combinations

Receiver / Reinforcement	Commercial frame	Frame mounted
	Casing frame	TE 240 3D FZ
	Steel frame	TE 240 3D SZ
	Steel door	TE 240 3D ST
	Aluminum frame	Specified by manufacturer

#### Installation Tools

Jig	Universal milling frame	
Frame	routing template	No. 5 251074 6
Door	routing template	No. 5 251075 6

#### Note

The load capacity mentioned above refers to the use of 2 hinges per door leaf with a height / width ratio of 2:1 (see page 46 for further detail).

For a minimum door panel thickness of 26 mm (1.024").

