

Schall-Ex® L-15/30 WS Pivot

- / pivot hinge door drop seal
- / sealing to the top and bottom
- / suitable with single-acting pivot doors
- / special roller actuator suitable for various frame designs
- / for opening in both directions



TECHNICAL DATA

Door type	hinged door, swing door
Door leaf material	timber
Application	exterior door, interior door
Usability	sound insulation, smoke protection, fire protection, accessibility
Actuation	single
Actuator	roll actuator
Carrier material	aluminium
Surface	mill finish
Surface colour	silver
Sealing profile material	self-extinguishing silicone
Sealing profile colour	grey
Door leaf	single leaf
Opening direction	DIN L or R

DIMENSIONS

Width x height	14,8 x 30 mm
Length min. - length max.	235 - mm
Standard lengths	833 mm, 958 mm, 1,083 mm, 1,208 mm
Shortening	125 mm
Shortening	from standard lengths
Travel	20 mm



FIXING

Installation	in-groove
Fixing	WS - fixing brackets
Press plate required	yes
Accessories incl.	5516
Maintenance-free	yes
For retrofitting	yes

Schall-Ex® L-15/30 WS Pivot

PERFORMANCE AND CERTIFICATION

Test cycles	200,000
MPA Qualitylabel	MPA NRW ZP 22-07 Klasse 4
UL	UL10C (R38166) Category J
EPD	EPD-ATD-36.0
Certifire	CF5675
AbZ	Z-6.100-2530



ART.NO.

1-946