

## 1. Identification

**Product identifier**

**WOOD PRODUCTS (PMDI BONDED)**

**Product list**

Temstock Free, Temstock Free MR, Temstock MR,

-----  
 UltraStock MDF produced with pMDI resin Shelving, UltraStock Free, UltraStock Free MR, Ultrastock HD

-----  
 DryGuard® OSB Sturd-I-Floor, DryMax®, Web stock, FiberStrong® Rim Board, DryMax® Cargo

-----  
 FiberStrong HD™ (Mill#s 531, 532, 530, 475),  
 Blue Ribbon® (Mill#s 531, 532, 530, 475),  
 Camouflage Panel Featuring Mossy Oak® (Mill#s 531, 475),  
 Realtree Camouflage Panel® (Mill#s 531, 475),  
 Thermostat® OSB Radiant Barrier Roof Sheathing (Mill# 531, 475),  
 ForceField® Weather Barrier System (Mill#s 475, 500, 531)

----- X-----  
 ----- X-----  
 ® is a Registered Trademark owned by or licensed to Georgia-Pacific Wood Products LLC  
 ™ is a Trademark owned by or licensed to Georgia-Pacific Wood Products LLC

**Other means of identification**

**SDS number**

GP-34B

**Recommended use**

Building Materials - Decorative

**Recommended restrictions**

None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name**

Georgia-Pacific Wood Products LLC

**Address**

133 Peachtree Street, NE  
 Atlanta, GA 30303

**Telephone**

Technical Information: 800.284.5347  
 (M)SDS Request: 404.652.5119

**E-mail**

MSDSREQ@GAPAC.COM

**Emergency phone number**

Chemtrec - Emergency: 800.424.9300

**Importer/Supplier/  
 Distributor**

**Company name**

GP North Woods LP

**Address**

327022 Highway 11  
 Englehart, ON P0J 1H0

**Telephone**

Technical Information: 705-544-2395  
 (M)SDS Request: 404.652.5119

**E-mail**

MSDSREQ@GAPAC.com

**Emergency phone number**

Chemtrec - Emergency: 800.424.9300

## 2. Hazard identification

**Emergency overview**

This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities (e.g., grinding, sanding, cutting, pulverizing) that reduce its particle size. Those hazards are described below.

**Physical hazards**

Combustible dusts Category 1

**Health hazards**

Eye irritation Category 2B

Sensitization, respiratory Category 1

Sensitization, skin Category 1A

Carcinogenicity Category 1A

Specific target organ toxicity following single exposure Category 3 respiratory tract irritation

Specific target organ toxicity following repeated exposure Category 1 (respiratory system)

**Environmental hazards**

Not classified.

**Label elements**



**Signal word**

Danger

**Hazard statement**

May cause an allergic skin reaction. Causes eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause cancer. Causes damage to organs (respiratory system) through prolonged or repeated exposure. If small particles of wood dust are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

**Precautionary statement**

**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Prevent dust accumulation and airborne dispersion of dust to minimize flash fire and explosion hazard. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

**Storage**

Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental information**

None.

**Other hazards**

None known.

### 3. Composition/information on ingredients

**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
WOOD/WOOD DUST		Not assigned	80 - 100
METHYLENE BISPHENOL ISOCYANATE (MDI)		101-68-8	1 - 5
POLYMERIC MDI (pMDI)		9016-87-9	1 - 5
2,4'-DIPHENYL METHANE DIISOCYANATE		5873-54-1	0.1 - 1
Other components below reportable levels			0.5 - 1.5

The specific chemical identity and/or percentage of composition has been withheld as a trade secret.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

**Inhalation**

Remove from area of exposure. If the affected person is not breathing, apply artificial respiration. If persistent irritation, severe coughing or breathing difficulty occurs, seek medical attention.

**Skin contact**

If irritation develops, wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact**

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Get medical attention if irritation develops and persists.

**Ingestion**

If wood or wood dust is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause an allergic skin reaction. Dermatitis. Rash. May cause respiratory irritation. Difficulty in breathing.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ). Apply extinguishing media carefully to avoid creating airborne dust. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
<b>Unsuitable extinguishing media</b>	Heavy water (or jet) stream may cause dust to become airborne and create a flash fire hazard or an explosive atmosphere.
<b>Specific hazards arising from the chemical</b>	Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	To avoid dust clouds, responders should use the extinguisher from as far away as possible and apply the extinguishing agent as gently as possible. The main considerations with hose stream operation are to avoid creating combustible dust clouds or introducing more air. In particular, the use of solid streams and direct dust pile hits can disperse dust into the air creating a potential flash fire hazard. The best way to apply water is in a medium to wide-pattern, as gently as possible. Responders should use a low nozzle pressure and loft the stream onto the burning material from as far away as the stream will reach.
<b>General fire hazards</b>	May form combustible dust concentrations in air.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Vacuum dust with dust ignition proof vacuum or wet sweep small wood pieces and dust; place in appropriate container for disposal. Gather larger pieces by an appropriate method. Reduce airborne dust by use of wet methods (e.g. water mist) and prevent scattering by moistening with water. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Dust can form an explosive mixture in air. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Minimise dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. If flash fire or explosion hazard is present, wear flame resistant clothing and face/head protection. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Use personal protective equipment as required. Ensure dust collection systems used for conveying combustible wood dusts are protected with and equipped with fire and explosion prevention and protection equipment. See NFPA 664 and NFPA 69 for further requirements, information and guidance.
<b>Conditions for safe storage, including any incompatibilities</b>	Store flat, supported and protected from direct contact with the ground. Store away from incompatible materials (see Section 10 of the SDS). Store in a cool dry place.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### ACGIH

Components	Type	Value	Form
WOOD/WOOD DUST	TWA	1 mg/m <sup>3</sup>	Inhalable fraction.

#### US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	TWA	0.005 ppm

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Type	Value	Form
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	TWA	0.05 mg/m <sup>3</sup>	
		0.005 ppm	
POLYMERIC MDI (pMDI) (CAS 9016-87-9)	TWA	0.07 mg/m <sup>3</sup>	
		0.005 ppm	
WOOD/WOOD DUST	TWA	3 mg/m <sup>3</sup>	Respirable particles.
		10 mg/m <sup>3</sup>	Total particulate.

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	Ceiling	0.01 ppm
	TWA	0.005 ppm

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Type	Value
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	TWA	0.005 ppm

#### Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Type	Value
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	TWA	0.051 mg/m <sup>3</sup>
		0.005 ppm

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

Components	Type	Value	Form
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	Ceiling	0.02 ppm	
	TWA	0.005 ppm	
WOOD/WOOD DUST	STEL	10 mg/m <sup>3</sup>	Dust.
		3 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Inhalable fraction.

#### Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended

Components	Type	Value	Form
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	TWA	0.051 mg/m <sup>3</sup>	

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended**

Components	Type	Value	Form
		0.005 ppm	
WOOD/WOOD DUST	TWA	10 mg/m <sup>3</sup>	Total dust.

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended**

Components	Type	Value
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)	15 minute	0.015 ppm
	8 hour	0.005 ppm

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Appropriate engineering controls</b>	Due to the fire and explosive potential of dust when suspended in air, precautions should be taken when material is used in any operation which may generate dust. Local exhaust, general dilution ventilation in enclosed areas, and explosion proof equipment is recommended. Use wet methods, if appropriate, to reduce airborne dust concentrations.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Safety glasses or goggles are recommended when using this product.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
<b>Other</b>	Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Safety shower/eye wash fountain is recommended in the workplace area.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using, do not eat, drink or smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**9. Physical and chemical properties**

<b>Appearance</b>	Rigid boards or panels
<b>Physical state</b>	Solid.
<b>Form</b>	Solid wood
<b>Colour</b>	Various
<b>Odour</b>	Not available.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	Not applicable
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	Not applicable
<b>Evaporation rate</b>	Not applicable
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	40 g/cm <sup>3</sup> for wood dust (Note: The LEL is equivalent to the Minimum Explosive Concentration (MEC) for the combustible dust. The MEC will vary with particle size of the wood dust. Recommend MEC testing for specific wood dust particle sizes generated or handled.)
<b>Explosive limit – upper (%)</b>	Not available
<b>Vapour pressure</b>	Not applicable
<b>Vapour density</b>	Not applicable
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble

<b>Partition coefficient (n-octanol/water)</b>	Not applicable
<b>Auto-ignition temperature</b>	> 204.4 - < 260 °C (> 399.92 - < 500 °F) for wood
<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Bulk density</b>	Not applicable
<b>Dust explosion properties</b>	
<b>St class</b>	1 Weak explosion.
<b>Explosive properties</b>	Not explosive.
<b>Flash point class</b>	combustible
<b>Oxidising properties</b>	Not oxidising.
<b>Specific gravity</b>	variable

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Dust accumulation, dispersion of dust in air, high temperatures, open flame, sparks, or other sources of ignition.
<b>Incompatible materials</b>	Strong acids, alkalies, oxidizing agents and drying oils.
<b>Hazardous decomposition products</b>	Thermal decomposition may emit irritating fumes or gases of carbon monoxide, carbon dioxide, aldehydes, or organic acids.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause irritation to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
<b>Skin contact</b>	May cause an allergic skin reaction.
<b>Eye contact</b>	Causes eye irritation.
<b>Ingestion</b>	Not applicable under normal conditions of use. May result in obstruction or temporary irritation of the digestive tract.

<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Dusts may irritate the respiratory tract, skin and eyes. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.
---	---

### Information on toxicological effects

<b>Acute toxicity</b>	Not known.
-----------------------	------------

Components	Species	Test Results
METHYLENE BISPHENOL ISOCYANATE (MDI) (CAS 101-68-8)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 10000 mg/kg
<b>Inhalation</b>		
<i>Vapour</i>		
LC50		0.178 mg/l
LC50	Rat	369 mg/m <sup>3</sup> , 4 Hours
<b>Oral</b>		
LD50	Rat	> 10000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Causes eye irritation.

## Respiratory or skin sensitisation

### Canada - Quebec OELs: Sensitizer

METHYLENE BISPHENOL ISOCYANATE (MDI) Sensitiser.  
(CAS 101-68-8)

### Canada - Saskatchewan OELs Hazard Data: Sensitiser

WOOD/WOOD DUST (CAS Not assigned) Sensitiser.

**Respiratory sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Skin sensitisation** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Wood dust generated from sawing, sanding or machining this product may cause nasal dryness, irritation, coughing and sinusitis. The International Agency for Research on Cancer (IARC), and National Toxicology Program (NTP) classifies wood dust as a carcinogen. This classification is based on the increased occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation noted insufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon, or rectum with exposure to wood dust.

### IARC Monographs. Overall Evaluation of Carcinogenicity

METHYLENE BISPHENOL ISOCYANATE (MDI) 3 Not classifiable as to carcinogenicity to humans.  
(CAS 101-68-8)

POLYMERIC MDI (pMDI) (CAS 9016-87-9) 3 Not classifiable as to carcinogenicity to humans.

WOOD/WOOD DUST (CAS Not assigned) 1 Carcinogenic to humans.

### US. National Toxicology Program (NTP) Report on Carcinogens

WOOD/WOOD DUST (CAS Not assigned) Known To Be Human Carcinogen.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** May cause respiratory irritation.

**Specific target organ toxicity - repeated exposure** Causes damage to organs (respiratory system) through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

### Partition coefficient n-octanol / water (log Kow)

METHYLENE BISPHENOL ISOCYANATE (MDI) 5.22

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations.

**Contaminated packaging** Empty packaging/container can be disposed in accordance with all applicable regulations.

## 14. Transport information

### TDG

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

## IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## 15. Regulatory information

### Canadian regulations

#### Controlled Drugs and Substances Act

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto Protocol

Not applicable.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Not applicable.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

**Issue date** 05-31-2017

**Revision date** 07-17-2023

**Version No.** 03

### Disclaimer

This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

### Revision information

Product and Company Identification: Product Codes  
Hazard identification: Prevention  
Hazard identification: Response  
GHS: Classification



# WOOD PRODUCTS (PMDI BONDED)

EN

## Danger

### Hazard statement

May cause an allergic skin reaction. Causes eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause cancer. Causes damage to organs (respiratory system) through prolonged or repeated exposure. If small particles of wood dust are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

### Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Prevent dust accumulation and airborne dispersion of dust to minimize flash fire and explosion hazard. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Dispose of contents/container in accordance with local/regional/national/international regulations.

FR-CA

## Danger

### Mention de danger

Peut provoquer une allergie cutanée. Provoque une irritation des yeux. Peut provoquer des symptômes allergiques ou d'asthme ou des difficultés respiratoires par inhalation. Peut irriter les voies respiratoires. Peut provoquer le cancer. Risque avéré d'effets graves pour les organes (le système respiratoire) à la suite d'expositions répétées ou d'une exposition prolongée. Si des petites particules de poussière de bois sont émises par des activités de transformation, de manipulation ou par d'autres moyens, elles peuvent former des concentrations de poussières combustibles dans l'air.

### Conseil de prudence

Se procurer les instructions avant utilisation. Ne pas manipuler avant d'avoir lu et compris toutes les précautions de sécurité. Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage. Porter une protection respiratoire. Ne pas respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols. Se laver soigneusement après manipulation. Ne pas manger, boire ou fumer en manipulant ce produit. Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail. Utiliser seulement en plein air ou dans un endroit bien ventilé. Éviter l'empoussièrement et la dispersion des particules de poussière dans l'air afin de minimiser les risques d'inflammation instantanée et d'explosion. Tenir à l'écart de la chaleur, des surfaces chaudes, des étincelles, des flammes nues et de toute autre source d'ignition. Ne pas fumer. EN CAS DE CONTACT AVEC LES YEUX: Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. Si l'irritation des yeux persiste : Demander un avis médical/Consulter un médecin. EN CAS DE CONTACT AVEC LA PEAU : Laver abondamment à l'eau. En cas d'irritation ou d'éruption cutanée : Demander un avis médical/Consulter un médecin. Enlever les vêtements contaminés et les laver avant réutilisation. EN CAS D'INHALATION : Transporter la personne à l'extérieur et la maintenir dans une position où elle peut confortablement respirer. En cas de symptômes respiratoires : Appeler un CENTRE ANTIPOISON/un médecin. EN CAS d'exposition prouvée ou suspectée : Demander un avis médical/Consulter un médecin. En cas d'incendie : utiliser un agent d'extinction approprié. Stocker dans un endroit bien ventilé. Entreposer à l'écart des substances incompatibles (consulter la section 10 de la FDS). Éliminer le contenu/réceptier conformément à la réglementation locale/régionale/nationale/internationale.

Manufacturer: / Company name: Georgia-Pacific  
Wood Products LLC / Address: 133 Peachtree Street,  
NE / Atlanta, GA 30303 / Telephone: Technical  
Information: 800.294.5347 / (MSDS Request:  
404.652.5119 / E-mail: MSDSREQ@GAPAC.COM /  
Emergency phone number: Chemtrec - Emergency:  
800.424.9300 / Supplier / Distributor:  
327022 Highway 11 / Englehart, ON P0J 1H0 /  
Telephone: Technical Information: 705-544-2395 / (M)  
SDS Request: 404.652.5119 / E-mail:  
MSDSREQ@GAPAC.com / Emergency phone  
number: Chemtrec - Emergency: 800.424.9300

 **Georgia-Pacific**

