



DryGuard® enhanced oriented strand board (OSB) is a multi-layered sub-floor product that has improved moisture resistance throughout the panel plus a black edge seal to help reduce moisture absorption. This means protection from the elements that helps avoid costly and time-consuming joint sanding. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays.

Available Sizes (Sized for 4' x 8')

Square Edge 3'-11⁷/₈" (1.216 m) x 7'-11⁷/₈" (2.435 m)

Tongue & Groove 3'-11¹/₂" (1.206 m) x 7'-11⁷/₈" (2.435 m)

Building Code Performance Categories, Panel Thickness

- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

Specifications

Length/Width Tolerance ±1/16" (±1.6 mm)

Straightness Tolerance ±1/16" (±1.6 mm)

Squareness Tolerance ±1/8" (±3.2 mm)

Testing Agency APA® – The Engineered Wood Association

Classification **Exposure 1** – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.

Code Fire Classification Class III or C

Flame Spread Rating 76-200, smoke-developed index <450

Building Code Compliance PS 2-18

Other Information

Forestry Certification DryGuard OSB panels are made from wood sourced through a system that is third-party certified to the Sustainable Forestry Initiative® procurement standard.



Product Warranty DryGuard OSB is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at buildgpc.com.

International Shipping To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. **Pallets made with engineered wood, including DryGuard® OSB, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing", www.PerformancePanels.com)

Formaldehyde Emissions DryGuard OSB contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the *Manufactured Home Construction and Safety Standards*.

Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Allendale, SC	531	29827	50 miles
Fordyce, AR	475	71742	100 miles

For installation instructions, specifications and warranty, please visit buildgpc.com/warranties | 800-284-5347



DryGuard, Georgia-Pacific and the DryGuard and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA and Sturd-I-Floor are registered trademarks of APA-The Engineered Wood Association. Sustainable Forestry Initiative, SFI, and the SFI logo are trademarks of Sustainable Forestry Initiative, Inc. ©2020 Georgia-Pacific Wood Products LLC. All rights reserved. Lit. Item #621516

Georgia-Pacific 133 Peachtree St., N.E., Atlanta, GA 30303