



HELIOS[®] AS-1X3TSPLIT DIGITAL OPTICAL AUDIO SPLITTER

 SALES 386-255-0234

PRODUCT OVERVIEW

This digital optical audio splitter allows the user to connect and distribute one digital optical output to three digital optical inputs without degradation. Ideal for connecting your digital audio source device to up to three device inputs, for use in home theaters, control rooms, production studios, A/V presentations, and meeting rooms.

- Splits one input signal to three SPDIF/optical audio output signals
- Supports LPCM2.0/DTS/DolbyTM AC3 audio
- Supports signal retiming
- Uses fiber optic cable
- Over-voltage protection
- Plug-and-play ready

SPECIFICATIONS:

Supported Digital Audio Formats.....	LPCM 2.0/DTX/Dolby TM AC3
Maximum Output Cable Distance	40 Meters
Power Supply Input	AC, 50Hz/60Hz, 100V - 240V
Power Supply Out	DC, 5V, 500 Ma
Maximum Current Draw.....	100 Ma
Operating Temperature Range	0 to 40 (C), 32 to 104 (f)
Dimension (L x W x H).....	.54 x .54 x 23.5 (mm), 2.2 x 2.2 x .9 (in)
Weight	35 (grams), 1.24 (oz)

