



# RealWoodFloors



## LAMINATE Watersafe Flooring



EuroCor920 is denser than traditional HDF, giving you more water protection, durability, and a better locking system.



The TriSeal system combines the EuroCor920, a water-tight REALock click system, and a 2mm waterproof seal to give you a watersafe floor.

### REALock Angle Tap System      AC4 Wear Rating      Matte Finish

	Wels	Lienz	Steyr
<b>THICKNESS</b>	8mm	10mm	12mm
<b>FACE</b>	EIR	Embossed	EIR
<b>WIDTH</b>	193mm (7.6")	193mm (7.6")	193mm (7.6")
<b>LENGTH</b>	1383mm (54.4")	1290mm (50.79")	1290mm (50.79")
<b>BEVEL</b>	Micro-Bevel	Micro-Bevel	Pressed
<b>PAD</b>	2mm Pad	No Pad	No Pad
<b>STC, IIC, ΔIIC</b>	51, 52, 22	51, 50, 20	51, 50, 20

#### FORMALDEHYDE EMISSION TESTING

Result: 0.2 mg HCHO/hm<sup>2</sup> - Formaldehyde emissions, determined by ISO 12460-3, is below the max permissible value (< 3.5 mg HCHO/hm<sup>2</sup>) for coated wood materials according to the Formaldehyde Ordinance valid in Austria & the DIBT Guideline 100 (EI).

#### ANTI-BACTERIAL PROPERTIES

The following values of the antibacterial activity were determined in the test according to ISO 22196:2007: *Staphylococcus aureus*: R > 3.9; *Escherichia coli*: R > 5.2. A clear antibacterial activity is given for R ≥ 1.

#### CERTIFICATIONS

