



RealWoodFloors



LAMINATE Watersafe Flooring



EuroCor920 is denser than traditional HDF, giving you more water protection, durability, and a better locking system.



The TriSeal system combines the EuroCor920, a water-tight REALock click system, and a 2mm waterproof seal to give you a watersafe floor.

REALock Angle Tap System

AC4 Wear Rating

Matte Finish

	Wels	Lienz	Steyr
THICKNESS	8mm	10mm	12mm
FACE	EIR	Embossed	EIR
WIDTH	193mm (7.6")	193mm (7.6")	193mm (7.6")
LENGTH	1383mm (54.4")	1290mm (50.79")	1290mm (50.79")
BEVEL	Micro-Bevel	Micro-Bevel	Pressed
PAD	2mm Pad	2mm Pad	No Pad
STC, IIC, ΔIIC	51, 52, 22	51, 50, 20	51, 50, 20

FORMALDEHYDE EMISSION TESTING

Result: 0.2 mg HCHO/hm² - Formaldehyde emissions, determined by ISO 12460-3, is below the max permissible value (< 3.5 mg HCHO/hm²) for coated wood materials according to the Formaldehyde Ordinance valid in Austria & the DIBT Guideline 100 (EI).

ANTI-BACTERIAL PROPERTIES

The following values of the antibacterial activity were determined in the test according to ISO 22196:2007: *Staphylococcus aureus*: R > 3.9; *Escherichia coli*: R > 5.2. A clear antibacterial activity is given for R ≥ 1.

CERTIFICATIONS

